UltraLights

Cylo 19412

project name:	
project location:	
specifier name:	
specifier location:	
quantity:	
fixture type:	

modifications:

Base Specs

19.5"h x 6"w x 4"d Opal Acrylic Bottom Diffuser

Notes

Dark Sky friendly available — **±$ Inquire**.
Marine grade primer available — **±$ Inquire**.



© 2021 UltraLights Lighting

Cylo 19412

standard finish:

BA - Bronze Age
BK - Black
BP - Black Pearl
CB - Cast Bronze
CH - Chestnut
CR - Chrome
DI - Dark Iron
EB - Empire Bronze
MB - Medieval Bronze
NB - New Brass
SB - Smokey Brass
SP - Satin Pewter
SS - Smoked Silver

lamping:

02: 16.8w Integrated LED, 2362 Initial Lumens, 3000K, 90 CRI, 120V, Standard Phase Dimming (120V), or 120-277V, 0-10V Dimming (277V), UL/cUL Wet (120V 0r 277V Must Be Specified)

04: 16.8w Integrated LED, 2362 Initial Lumens, 3000K, 90 CRI, 120V-277V, 0-10V Dimming, UL/cUL Dry/Damp

10: Wattage Restriction Label - 2 x E26 for LED Retrofit 20W max ea - A-Type, 120V, Standard Phase Dimming, UL/cUL Dry/Damp

14: 16.8w Integrated LED, 2362 Initial Lumens, 3000K, 90 CRI, 120V, Standard Phase Dimming, UL/cUL Dry/Damp

standard diffuser:

OA - Opal Acrylic

© 2021 UltraLights Lighting