

Icon 23523

project name:

project location:

specifier name:

specifier location:

quantity:

fixture type:



Base Specs


12"dia. x 2.25"d.

Opal Acrylic Diffuser

Up to 4 custom characters included

Notes

Available with braille and raised number placard — ±\$ Inquire
Custom logos available — ±\$ Inquire
Marine grade primer available — ±\$ Inquire.







^{*} example of optional braille and raised character placard. (location, size, and specifics TBD)







Icon 23523

standard finish:

BA - Bronze Age

BK - Black

CB - Cast Bronze

DI - Dark Iron

NB - New Brass

SP - Satin Pewter

lamping:

02: 23.57w Integrated LED, 3774 Initial Lumens, 3000K, 90 CRI, 120V, Standard Phase Dimming (120V), or 120-277V, 0-10V Dimming (277V), UL/cULWet(120V or 277V Must Be Specified)

04: 17.9w Integrated LED, 3043 Initial Lumens, 3000K, 90 CRI, 120V-277V, 0-10V Dimming, UL/cUL Dry/Damp

14: 23.57w Integrated LED, 3774 Initial Lumens, 3000K, 90 CRI, 120V, Standard Phase Dimming, UL/cUL Dry/Damp

standard diffuser:

OA - Opal Acrylic



